


SEGA™

GAME GEAR™

COLOR PORTABLE VIDEO GAME SYSTEM™

MAINTENANCE MANUAL

EUROPE



August, 1992
SEGA ENTERPRISES, LTD.
Rev. A

GAME GEAR
MAINTENANCE MANUAL
EUROPE

◆ INDEX ◆

1. BLOCK DIAGRAM
2. ASSEMBLY DRAWING
 - 2-1. GENERAL REFERENCE NUMBER LIST
 - 2-2. ASSEMBLY LIST
 - 1001 BOTTOM CASE ASSEMBLY 1
 - 1002 BOTTOM CASE ASSEMBLY 2
 - 1003 MAIN BOARD ASSEMBLY
 - 1004 BOTTOM CASE ASSEMBLY 3
 - 2-3. PROCEDURE OF DISASSEMBLY AND ASSEMBLY
3. SPARE PARTS LIST
4. ACCESSORIES LIST
5. PCB REPAIR PROCEDURE
6. SOFT & HARD CHECK MANUAL

7. PARTS SPECIFICATION

7-1. MAIN BOARD IC1 IC Z80A TMP84C00AM-6
7-2. MAIN BOARD IC2 IC CUSTAM VDP 315-5377
7-3. MAIN BOARD IC3 IC CUSTAM SCA 315-5378A
7-4. MAIN BOARD IC4 IC μ PD4364G-15L
7-5. MAIN BOARD IC5 IC HM6256BLFP-12
7-6. MAIN BOARD IC6 IC μ PC358G2
7-7. DC-DC CONV. BOARD IC1 IC MB3775FP-G-BND
7-8. SOUND BOARD IC1 IC TDA2822M

8. PARTS LIST OF PCB

8-1. IC BD GG MAIN EUROPE
8-2. IC BD GG MAIN EUROPE B
8-3. IC BD GG DC-DC CONV. EUROPE
8-4. IC BD GG DC-DC CONV. EUROPE B
8-5. IC BD GG SOUND EUROPE
8-6. IC BD GG SOUND EUROPE B

9. SCHEMATIC DIAGRAM

9-1. PC BD GG MAIN EUROPE
9-2. PC BD GG MAIN EUROPE SCA B
9-3. PC BD GG DC-DC CONV. EUROPE
9-4. PC BD GG DC-DC CONV. EUROPE SCA B
9-5. PC BD GG SOUND EUROPE
9-6. PC BD GG SOUND EUROPE SCA B

10. MOUNT DIAGRAM


10-1a. IC BD GG MAIN EUROPE Comp Side
10-1b. IC BD GG MAIN EUROPE Sold Side
10-2a. IC BD GG MAIN EUROPE SCA B Comp Side
10-2b. IC BD GG MAIN EUROPE SCA B Sold Side
10-3a. IC BD GG DC-DC CONV. EUROPE
10-3b. IC BD GG DC-DC CONV. EUROPE SCA B
10-4a. IC BD GG SOUND EUROPE
10-4b. IC BD GG SOUND EUROPE SCA B

GAME GEAR

EUROPE

BLOCK DIAGRAM

GameGear ブロック図...



11. PCB DESIGN SPEC.

11-1a.	PC	BD	GG	MAIN BOARD	COMP SIDE MARK
11-1b.	PC	BD	GG	MAIN BOARD	SOLD SIDE MARK
11-1c.	PC	BD	GG	MAIN BOARD	COMP SIDE LAYER
11-1d.	PC	BD	GG	MAIN BOARD	SOLD SIDE LAYER
11-2a.	PC	BD	GG	DC-DC CONV. BOARD	COMP SIDE MARK
11-2b.	PC	BD	GG	DC-DC CONV. BOARD	SOLD SIDE MARK
11-2c.	PC	BD	GG	DC-DC CONV. BOARD	COMP SIDE LAYER
11-2d.	PC	BD	GG	DC-DC CONV. BOARD	SOLD SIDE LAYER
11-3a.	PC	BD	GG	SOUND BOARD	COMP SIDE MARK
11-3b.	PC	BD	GG	SOUND BOARD	SOLD SIDE MARK
11-3c.	PC	BD	GG	SOUND BOARD	COMP SIDE LAYER
11-3d.	PC	BD	GG	SOUND BOARD	SOLD SIDE LAYER

GAME GEAR FOR EUROPE


GENERAL REFERENCE NUMBER LIST

REF NO.	PART NO.	DESCRIPTION	QTY
001	610-5212	ASSY TOP CASE GG USA	(1)
	610-5212-01	ASSY TOP CASE GG USA 01	(1)
002	610-5255	ASSY BOTTOM CASE GG MULTI	(1)
	610-5255-01	ASSY BOTTOM CASE GG MULTI 01	(1)
003	253-6362	CLEAR PLATE GG	(1)
	253-6434	CLEAR PLATE GG INMOLD	(1)
004	253-6363-01	PAD GG 01	(1)
	253-6363-03	PAD GG 03 (CONTACT TYPE)	(1)
005	253-6364	BUTTON 1 GG	1
006	253-6365	BUTTON 2 GG	1
007	253-6366	START BUTTON GG	1
008	253-6368	BATT LID LEFT GG	1
009	253-6369	BATT LID LIGHT GG	1
010	253-6378	POWER KNOB GG	1
011	253-6401	10P CONN COVER GG	1
101	837-7994	ASSY IC BD GG EUROPE	(1)
	837-7994B	ASSY IC BD GG EUROPE B	(1)
102	837-7997	IC BD GG DC-DC CONV.EUROPE	(1)
	837-7997B	IC BD GG DC-DC CONV.EUROPE B	(1)
103	837-7998	IC BD GG SOUND EUROPE	(1)
	837-7998B	IC BD GG SOUND EUROPE B	(1)
201	029-0069	TAP SCR PH 2.6*10 BLK	6
202	012-0312	TAP SCR PH 3*12	2
203	012-0206	TAP SCR PH 2*6	10
204	029-0326	TAP SCR LH-3 2.6*10 BLK	1
301	509-5334	RUBBER CONTACT GG 4P	(1)
	509-5334-01	RUBBER CONTACT GG 4P 01	(1)
302	509-5335	RUBBER CONTACT GG 1P	3
303	601-6428	LCD CUSHION GG	1
304	253-6422	BATT. BLADE COVER GG	1
305	250-6243	SUPPORT PLATE GG 01	1

GAME GEAR

EUROPE

ASSEMBLY DRAWING



ASSEMBLY LIST FOR GAME GEAR EUROPE

INDEX

1001 BOTTOM CASE ASSEMBLY 1

1002 BOTTOM CASE ASSEMBLY 2

1003 MAIN BOARD ASSEMBLY


1004 BOTTOM CASE ASSEMBLY 3

PARTS LIST FOR GAME GEAR EUROPE

1001 BOTTOM CASE ASSEMBLY 1

REF NO.	PART NO.	DESCRIPTION	QTY
008	253-6368	BATT LID LEFT GG	1
009	253-6369	BATT LID LIGHT GG	1
201	029-0069	TAP SCR PH 2.6*10 BLK	6
204	029-0326	TAP SCR LH-3 2.6*10 BLK	1

1001 BOTTOM CASE ASSEMBLY 1




PARTS LIST FOR GAME GEAR EUROPE

1002 BOTTOM CASE ASSEMBLY 2

REF NO.	PART NO.	DESCRIPTION	QTY
NON PARTS ASSEMBLY.			

1002 BOTTOM CASE ASSEMBLY 2




PARTS LIST FOR GAME GEAR EUROPE

1003 MAIN BOARD ASSEMBLY

REF NO.	PART NO.	DESCRIPTION	QTY
101	837-7994	ASSY IC BD GG EUROPE	(1)
	837-7994B	ASSY IC BD GG EUROPE B	(1)
202	012-0312	TAP SCR PH 3*12	2
203	012-0206	TAP SCR PH 2*6	6

1003 MAIN BOARD ASSEMBLY




PARTS LIST FOR GAME GEAR EUROPE

1004 BOTTOM CASE ASSEMBLY 3

REF NO.	PART NO.	DESCRIPTION	QTY
002	610-5255	ASSY BOTTOM CASE GG MULTI	(1)
	610-5255-01	ASSY BOTTOM CASE GG MULTI 01	(1)
102	837-7997	IC BD GG DC-DC CONV.EUROPE	(1)
	837-7997B	IC BD GG DC-DC CONV.EUROPE B	(1)
103	837-7998	IC BD GG SOUND EUROPE	(1)
	837-7998B	IC BD GG SOUND EUROPE B	(1)
203	012-0206	TAP SCR PH 2*6	8
305	250-6243	SUPPORT PLATE GG 01	1

1004 BOTTOM CASE ASSEMBLY 3



PROCEDURE OF DISASSEMBLY AND ASSEMBLY OF GAME GEAR

1.DISASSEMBLY

PROCESS 1 : Removing screw from Bottom Case.

- 1) Upset the unit.
- 2) Remove Battery Lid.
- 3) Remove screws (201 and 204)
- 4) Remove a screw (204)

PROCESS 2 : Removing Bottom Case.

- 1) Hold up Bottom Case to the direction (A) and make the open condition.
- 2) Remove the connector of DC converter Board fixed on the Bottom Case.
- 3) Remove two connectors of Sound Board fixed as above.

PROCESS 3 : Removing the Main Board.

- 1) Remove the screws (two 202 and six 203) and Main Board from Top Case.

PROCESS 4 : Removing Support Plate, DC-DC Conv. Board and Sound Board.

- 1) Remove 4 screws (203).
- 2) Remove Support Plate from Bottom Case.
- 3) Remove 2 screws (203).
- 4) Remove DC-DC Conv. Board from Bottom Case.
- 5) Remove 2 screw (203).
- 6) Remove Sound Board as above.

2.ASSEMBLY

PROCESS 1 : Setting Support Plate, DC-DC Conv. Board and Sound Board.

- 1) Set the Sound Board, DC-DC Conv. Board and Support Plate to Bottom Case using 8 screws (203).

PROCESS 2 : Setting of Main Board.

- 1) Spray surface of inside clear plate with static proof liquid.
- 2) Carefully observe and take away dust inside clear plate and Top Case using air gun in clean place.
Set each Button and Rubber contact to normal position.
- 3) Set LCD cushion along to the place of Bosses in Top Case.
- 4) Lead Speaker Cable outside of Boss of Top Case.
- 5) Setting of Main Board.
Case 1 After exchange of LCD
Take off protection film of LCD.
Case 2 Others
Clean surface of LCD using air gun.
Set the Main Board inside and along to the Bosses of Top Case.

Note : At the setting of Main Board, it is important to set it as quick as possible to prevent the stick of dust on the surface of LCD and clear plate.

6) Fix screw 6 of 203 and 2 of 202.

PROCESS 3 : Setting of Bottom Case.

- 1) Correct 2 connectors from Main Board to Sound Board and 1 connector from Main Board to DC-DC Conv. Board.
- 2) Firmly set Bottom Case to Top Case taking care not to pinch cables in the edge of cases.

PROCESS 4 : Screwing Bottom Case.

- 1) Upset the unit.
- 2) Fix a screw (204).
- 3) Fix 6 screws (201).
- 4) Fix Battery Lids.

GAME GEAR

EUROPE

SPARE PARTS LISTS

GAME GEAR SPARE PARTS LIST FOR EUROPE

No	PARTS No.	DESCRIPTION	R1	R2	R3	R4
1	610-5212	Assy Top Case GG USA	●		●	
	610-5212-01	Assy Top Case GG USA 01		●		●
2	610-5255	Assy Bottom Case GG MULTI	●		●	
	610-5255-01	Assy Bottom Case GG MULTI 01		●		●
3	253-6362	CLEAR PLATE GG	●	●		
	253-6434	CLEAR PLATE GG INMOLD	●	●	●	●
4	509-5334-01	RUBBE CONTACT 4P 01	●	●		
	509-5334	RUBBER CONTACT 4P			●	●
	509-5335	RUBBER CONTACT 1P	●	●	●	●
5	837-7994	ASSY IC BD GG EUROPE (837-7995)	●	●	●	●
	837-7994B	ASSY IC BD GG EUROPE (837-7995B SCA B)	●	●	●	●
6	837-7997	IC BD GG DC-DC CONV.EUROPE	●	●	●	●
7	837-7998	IC BD GG SOUND EUROPE	●	●	●	●

Note:

R1: PARTS No.610-5224 ASSY GG MULTI
 R2: PARTS No.610-5224-01 ASSY GG MULTI 01
 R3: PARTS No.610-5358 ASSY GG MULTI CONTACT TYPE
 R4: PARTS No.610-5358-01 ASSY GG MULTI CONTACT TYPE 01

GAME GEAR

EUROPE

ACCESSORIES LIST

GAME GEAR ACCESSORIES LIST FOR EUROPE

No	PARTS No.	DESCRIPTION
1	MK-2101-05	TV TUNER PAC (PAL-I:ENGLAND)
	MK-2101-18	TV TUNER PAC (PAL-B:ITALY/PAL-G:GERMANY)*ZZF APPROVAL
	MK-2101-20	TV TUNER PAC (PAL-B:ITALY/PAL-G:GERMANY)*ZZF NOT APPROVAL
2	MK-2102-50	GEAR TO GEAR CABLE
3	MK-2104-50	CAR ADAPTOR
4	MK-2105-50	BATTERY PAC
5	MK-2106-50	AV CABLE
6	400-5122A	AC ADAPTOR AC220V/DC10V 1.2A
	400-5122B	AC ADAPTOR AC220V/DC10V 1.2A
	400-5127	AC ADAPTOR AC240V/DC10V 1.2A
	400-5127A	AC ADAPTOR AC240V/DC10V 1.2A


GAME GEAR

EUROPE

PCB REPAIR PROCEDURE

PCB REPAIR PROCEDURE

PCB REPAIR FLOW CHART



GAME GEAR

EUROPE

SOFT & HARD CHECK MANUAL


SOFT CHECK MANUAL

GAME GEAR SOFT CHECK FLOW



CHECK CARTRIDGE- - -

COMMUNICATION CABLE --> START


HEADPHONE-----J



GAME GEAR SOFT CHECK MANUAL



SCREEN 1



If the power is turned on, the screen shown on left is displayed.


Make sure that the LED location is correct and the LED is lit.

Be sure that the mark ▶ under START moves in the right direction.


Check 1. Check of 4-key pad & headphone sound

Press button-1 while pressing an optional direction of the 4-key pad ; then, the sound is heard from the left of the headphone.


In the same manner, press button-2 ; then, the sound is heard from the right of the headphone.




Right + ① button



Right + ② button



Lower Right



Upper Right

Operate "Right + Button ①, ②", "Up + Button ①, ②", "Left + Button ①, ②", "Down + Button ①, ②" and check if the clicking feeling of the PAD button ①, ② is normal, if the headphone sound is heard from left and right respectively, and if the quality of the sound is normal, etc.

Go on the checking in the slant direction in the order of lower right, upper right, upper left and lower left.

CHECK 2. Check of the built-in speaker

Remove the headphone pin and perform the same manner as the check 1.

(Check in the slant direction canceled.)


Move the sound volume to the maximum and minimum and check if the sound is interlocked and the volume sound is smooth.

If there is no problem in the above check, switch to the next screen.

(Press START)

* At this point, check if there is any abnormality in the operation of the START button or in the click feeling.

SCREEN 2



CHECK 3. Check of brightness (Contrast)

Move the brightness volume to the maximum and minimum and check if the light volume is interlocked to the movement and if there is any light unevenness, LCD stain, damage, spots, etc.


At this point, press the pad and buttons the respective colors and LCD (spot, dust, difference defects, etc.)

1. Red. 2. Yellow 1+2. Black

Upper: Green Lower: Green Left: Purple
Right: Pink

If there is no problem in the above check, switch to the next screen. (Press START)

SCREEN 3



CHECK 4. Color check ①

Vertical color patterns appear.

Check if the hues are normal, or if there is any LCD stain, scratch, and spot etc.

If there is no problem in the above check, switch to the next screen. (Press START)

GG CHECK PROGRAM SPECIFICATION

CHECK PROGRAM AND ORDER

(I) Check the following 3 items in the state of black screen until the check screen (Fig.1) appears after turning on the power. If an error occurs, the error messages as shown in Table 1 appear in white characters on the red background. At this point, terminate the checking and stop further checking work.

- ① Scratch RAM R/W check
- ② V_RAM R/W check
- ③ Communication port check (Parallel & Serial)

(II) If the above check (I) is O.K., check the following 5 items as the check screen (Fig.1) appears.

- ④
 - JOY port check
 - Color RAM check
 - Spright check
 - Sound check
 - Cross-talk check




Fig. 1 Check sreen

[CHECK METHOD OF EACH ITEM]

SCRATCH RAM CHECK

- ① Read after writing all 55h to C000h~DFFFh.
- ② Read after writing all AAh to C000h~DFFFh.
- ③ Write 1FFFh to C000h and C001h.
Write 1FFEh to C002h and C003h.

↓

Write 1000h to DFFEh and DFFFh.
Read the above values respectively.

V_RAM CHECK

- ① Read after writing all 55h to 0000h~3FFFh.
- ② Read after writing all AAh to 0000h~3FFFh.
- ③ Write 3FFFh to 0000h and 0001h.
Write 3FFEh to 0002h and 0003h.

↓

Write 2000h to 3FFEh and 3FFFh.
Read the above values respectively.

COMMUNICATION PORT
CHECK

- ① Serial communication check
- ② Parallel Communication check

{ The exclusive adaptor is required as checking is done by one(1) set. }

JOY PORT CHECK

- ① Checking of the direction button (↑ ↓ ↔),
A&B buttons and START button (if the button
is pressed, the corresponding portion turns red.)

COLOR RAM CHECK

- ① Displaying of the 32 (colors) squares

SPRIGT CHECK

- ① Move the arrow in right and left direction
with spright definition.

SOUND CHECK

- ① Check the (pseudo) stereo (left, right or left-right
simultaneousl by using an earphone). Three tones and
one noise are allocated to the direction buttons
(↑ ↓ ↔) and the distribution to left/right by stereo
is allocated to the A/B butons. For example,
if the (↑) button is turned on while pressing
the A button, the tone-1 is delivered to the left.
(If the left-right button is pressed in this state,
the output is made o the both sides.)

CROSS-TALK CHECK

-① The white square is displayed on the black background. Check the extent of the cross-talk at the upper/lower parts.

Table-1. ERROR MESSAGE

S-RAM 不良 (S-RAM DEFECT)

.....At the point of scratch RAM check

V-RAM 不良 (V-RAM DEFECT)

.....At the point of V - RAM check

通信不良 (COMMUNICATION DEFECT)

.....At the point of communication port check

パッド不良 (PAD DEFECT)

..... At the point of JOY port check

Game Gear Hardware Checker
(Parts No. 610-5176)

Issued on: Aug. 4, 1992
SEGA JAPAN.

1. General

This checker is designed to check the Printed Circuit Board Assembly for Game Gear.

2. Operation Flow

1. Connect the Checker to Pin Tool by using the connectors (14 pin, 24 pin, 36 pin, 2 pin, SUB PCB, START SW, SW2)
2. Connect the Checker to TV by using Video Cable
3. Connect the checker to 100V outlet.
4. Turn the Checker Power on.
(“SET INSPECTED TARGET” is indicated on TV screen.)
5. Set the PCB Assy on Pin Tool.
6. Turn the “START SW” on
(Screen should be fade out and “CHECK VOLUME” is indicated on TV screen after about 2sec, then “VOLUME CHECK” is indicated on LCD screen)
7. Rotate the Volume Adjustment on PCB and check the “Level Gauge” on Volume Screen adjusted between 0 - 8 and also confirm the Indication of color Bar change the color from white to black.
LED on PCB should be lit on.
8. By pressing “SW2”, Finish the Volume Check function and “CHECK LCD” on TV and Red Color Bar on LCD are indicated.
Then color bar should be change color from Red → Green → Blue by pressing “SW2”
9. Press “SW2” again and confirm the “CHECK LED” is indicated on both TV and LCD. In this condition, LED should blink.
10. After confirm the LED blinking, press “SW2” to change the screen for TV Mode Check. Confirm both LCD and TV has same indication in this condition. Then press “SW-2” again to change the TV screen to Error Check (Horizontal/Vertical Direction = Color Bar)
* In case of no error “TEST 1 OK” and in case of error “ERR POINT” and Error Point should be indicated.


11. Turn "START SW" off and remove PCB from Pin Tool
12. Repeat above procedure ⑤ - ⑪.

Note


1. If turn the "START SW" on without setting or improper setting of PCB Assy on Pin Tool or POWER SHORT ERROR is found, Checker will stop inspection and indicate "WARNING POWER SHORT ERROR CHECK STOP" on TV screen
2. If "BUS ERR" is found, Checker do not execute item 7 and 8.
3. In case the Error other than "POWER SHORT ERROR" is found, all errors are indicated on Error Check Screen during TV Mode check. (As to Errors, Please refer to Error Message)
4. As to Volume Check, LCD Color Bar check, LED Check & TV Mode Screen Check should be visible inspection (Item 7, 8, 9 & 10)
5. Checker program can not perform the Visible Inspection.

3) Check Flow


Check Item (SYSTEM)




Check Item (TARGET)



TV SCREEN



LCD SCREEN



4) Error Message

Errors except for "POWER SHORT ERROR" are discovered during inspection - shall be indicated on TV screen as "ERR POINT" after inspection. (If there is no error, "TEST 1 OK" shall be indicated)

Error message is constructed from Main Error Message (Error Portion) and Sub Error Message (Error status or Further to define error portion)

(1) Error Indication

I. Standard Error Indication

ERR		POINT	
Main Error Message ↗		↗ Sub Error Message	
POWER	H	S-RAM	
T5V	L	V-RAM	
+2.5V	H	JOYSTICK	↗ Main Error Message
VREF	L	012345	↗ Sub Error Message
VRES	H	CPU SIGNAL	
VONF	L	012345	
T34V	H	COMM	
FL-H	L	VOL OVER	
CURNT	L	ON RST FST	
		OFFSET	
		SLW	
			↗ Sub Error Message
			↗ Main Error Message
CHECK ERRORS = * * ↗ Total Error			

II Bus Error Indication

ERR Main Error Message		POINT Sub Error Message
POWER	H	BUS \approx BUS ERROR
+5V	L	
+2.5V	H	
VREF	L	ERR
VRES	H	
VONF	L	
+3.4V	H	
FL-F	L	
FL-V	H	
CURNT	L	ON RST FST
		OFF RST SLW
		└─ Sub Error Message
		└─ Main Error Message
CHECK ERRORS = * * \approx TOTAL ERROR		

In case of short circuit of Address, Data Bus and/or CN1, "Wire disconnection", "Pin Tool or Sub PCB Assy missetting" or "Defective CI" function check of PCB Assy shall not be executed to eliminate the uncontrolled program run. (Therefore, inspection between DUAL ROM check and LCD check shall not be performed.)

2) . Power Short Error Indication .

In case of short circuit on PCB Assy or improper setting of PCB Assy, stop inspection to protect the PCB damage and indicate the following message

WARNING
POWER SHORT ERROR
CHECK STOP

If turn "START SW" off, screen returns to original ("SET INSPECTION TARGET").

(3) Error Message and Defective Portion

<u>No.</u>	<u>Main Error</u>	<u>Sub Error</u>	<u>Defective Portion</u>	<u>Note.</u>
Ⓐ	POWER	H or L	Short Circuit or Improper setting	Due to POWER SHORT ERROR, this is not indicated as long as program runs correctly.
Ⓑ	T5V	H or L	Battery Board (837-7399-01)	ANALOG 5V signal is not within standard Voltage.
Ⓒ	+2.5V	H or L	R48, R49, C48	+2.5V is not within standard Voltage.
Ⓓ	VREF	H or L	Battery Board IC3-PIN30	Vref signal is not within standard Voltage.
Ⓔ	VRES	H or L	Battery Board IC3-PIN32, R50, R51, R52 D4, C49	Vres signal is not within standard Voltage.
Ⓕ	VONF	H or L	Battery Board IC3-PIN31, R50, R51, R52 D4, C49.	Vonf signal is not within standard Voltage.
Ⓖ	T34V	H or L	Battery	T34V signal is not within standard Voltage.
Ⓗ	FL-F	H or L	Around T1, Q3, Q4	FL Frequency is out of spec.
Ⓘ	FL-V	H or L	"	FL Voltage is out of spec.
Ⓣ	CURNT	H or L	IC2, IC5, Resistor, Capacitor, Soldering of IC, Misselling.	Current is out of spec.
Ⓚ	S-RAM	Non	IC4, IC2, IC1	Internal RAM operate correctly?
Ⓛ	V-RAM	Non	IC5, IC2, IC1.	V-RAM operate correctly?
Ⓜ	JOYSTICK	0-5	IC3, Pattern on PCB	Data can transfer to JOYSTICK PORT * 1
Ⓝ	CPU SIGNAL	0-5	IC1, IC3, X1 Misccontact on Pin Tool	Check CPU Signal * 1
Ⓞ	COMM	0~6	IC3, IC2, EM1~EM8, X1	Communication done in proper way. * 1.

① VOL OVER Non IC3, IC6, IC2
SOUNDBOARD (837-7400-01)

SOUND output is more than
Spec. ("LEVEL OVER" is
indicated on Volume Check
Screen)

② ON RST FST or
SLW IC3, Battery Board RD~52
D4, C49 inspection did
not execute correctly

Reset signal is not generated
for required period during
power on stage.

③ OFF RST FST or
SLW IC3, Battery Board RD~52,
D4, C49 inspection did
not execute correctly.

"

(4) Sub Error Message

I. H or L (A ~ J)

H: Inspected Value is higher than spec. (High)

L: Inspected Value is Lower than spec. (Low)

II. FST or SLW (Q, R)

FST: During Power On or off stage, Reset signal raises or drops earlier than spec. (FAST)

SLW: During Power on or off stage, Reset signal raises or drops slower than spec. (SLOW)

III JOYSTICK 0 ~ 5 (M)

<u>SUB ERROR</u>	<u>Defective Partion</u>	<u>Note.</u>
0	IC3, Patten on PCB	PAUSE SW donot became all on condition
1	IC3, Patten on PCB	PAUSE SW do not became all off condition
2	IC3, Patten on PCB	Upper, Right, SW1 donot became on
3	IC3. Patten on PCB	Lower, Left, SW 2 donot became on.
4	"	PAUSE/START SW donot became on
5	"	PAUSE/START SW donot became off.

7 CPU SIGNAL 0~5 (㊟)

<u>SUB ERROR</u>	<u>Defective Portion</u>
0	IC1 - PIN20
1	IC1 - PIN27
2.	IC1 - PIN28
3.	IC3 - PIN35, X1
4	IC1 - PIN24, R2
5.	IC1 - PIN24, R1

Note.

IDRQ does not generate correctly.
 M1 does not generate correctly.
 RFSH does not generate correctly.
 CCLK does not generate correctly.
 WAIT does not generate correctly.
 BUSRQ does not generate correctly.

Communication 1~6 (㊟)

<u>SUB ERROR</u>	<u>Defective Portion</u>
0	IC3, CN2, EM1~EM8
1	IC3, CN2, EM1~EM8
2	IC3, CN2, EM1~EM8
3	IC3, CN2, EM1~EM8
4	IC3, CN2, X1
5	IC3, CN2, X1
6	IC3, CN2, X1

Note.

Input data does not match with instructed value.
 Cannot input data.
 Output data does not match with instructed value.
 Cannot output data.
 Cannot output 4800 BPS.
 Cannot output 2400 BPS.
 Cannot output the data with 2400 BPS.

Note.

In case 0~3 and 4 error is indicated, 0~3 sub error is happened during data input/output with 4800 BPS

⑤ Note about sub Error.

- I. H and L Sub Error does not generate at the same time for 1 Main Error.
- II. FST and SLW Sub Error does not generate at the same time for 1 Main Error.
- III. ① ~ ③, ④ and ⑤ error is generated, Hor L, FST or SLW Sub Error should be generated after Main Error. So, these error is making 1 error with the combination of Sub and Main Error.
Therefore, if SUB Error is not generated after Main Error, there may be some chance program does not run properly.
- IV. 0 ~ 6 Sub Error generate for ①, ② and ③ Main Error, 1 numeric is match for 1 Error. Therefore, there is possibility more than 1 numeric is generated. And as explained in above item III, Sub Error and Main Error is always making pair.

Visual Check.

Please perform the Visual Check on the following 4 items. And, Visual Check portions are "LED Screen on Checker" and "LED on Checking PCB"

Checker program did not have this function.

No	Visual Check Point	Check Item	Defective Portion
①	LCD Screen (Volume Check)	When turn the VOL adjustment on PCB, check the level gage in "VOLUME CHECK" screen moves 0-8 / 8-0.	SOUND BOARD (837-7400-01, IC6, IC3, IC2, R3~R10, C8~C11).
②	LCD Screen (LCD Check)	Check the color bar changes the color Red → Green → Blue by pressing SW2. (Specially on Red Color Bar, Black line at color changing portion should not be observed)	IC3, IC2, IC5
③	LED (LED CHECK)	check LED-blinking on PCB at "CHECK LED" screen	LD1, IC3, R11 Battery PCB (837-7399-01)
④	LCD Screen (TV MODE CHECK)	Check there is no difference between LED screen and TV screen in TV mode	IC3, CN1

5) Others

① Meter Relay.

Meter Relay observes the power consumption of GT.

Setting Value should be in between "LOW side = +0360" and "HI SIDE = +0430".

This setting has enough allowance even if parts specification value may fluctuate. So, please try to set above gap as much as narrow.

This error is indicated as ① CURNT on screen.

② CN2

Inspection starts as soon as CN2 is activated. Please make sure CN2 is activated after "Cam SW makes contact" and "Pin or Pin Tool contact to points complibly".

③ CN4

Please connect the Push SW which is used at Inspection. And Pin # 1 and # 3 should be used.

Moment Type Switch should be used also.

④ Radiator for IC2 & IC9

Please mount the proper radiator on IC2 (uPC 317), IC9 is not required to mount any radiator.

Please do not use the radiator jointly between IC2 & IC9.

⑤ Pattern Correction

The following pattern layout modifications should be required on 837-7617 Board.

- $\pm V$ of AC/12VDC and AC/5VDC should be jumpered at both side of PCB
- 10 pin of IC5, IC8 and IC12, should be disconnected and connected to pin # 11
- Add 74HC4066 and connect the pin # 1 to Pin # 1 of IC36, Pin # 2 to Pin # 24 of CN3 and pin # 13 to Pin # 1 of IC38.
- Cut the pattern between Pin # 1 of IC37 and Pin # 24 of CN3
- Disconnect Pin # 64 of IC28 and jumper to pin # 65 line.
- Jumper the pin # 14 of IC44 to GND
- Disconnect Pin # 3 and # 45 of IC41 and these disconnected lines should be connected to Pin # 48 through 1K Ω Resistors. And disconnected Pin # 3 should be connected the line used to connect with Pin # 45 through 120 Ω Resistor.

Disconnected Pin #45 should be connected to the line used to connect with Pin #3 through 120 Ω Resistor.

) Caution


1. Since more than 300 V high Voltage line on P37-7619 PCB Assy (ASSY EG CHECKER LCD). Please handle very carefully.
2. 36 wire cable length for Pin Tool should be minimized!
If cable is too long, you may observe LCD screen interference.
3. Please turn on the checker 10 minute before inspection.

GAME GEAR

EUROPE


PARTS SPECIFICATION

ピン配置図(上面図)



SSOP40-P-450

単位 : mm



270289

ピン名称と機能

ピン名称	ピン数	入/出力 3ステート	機 能
A0~A15	16	出 力 3ステート	16ビットのアドレスバス。 アクセスするメモリや入出力ポートのアドレス指定を行います。リフレッシュ期間中はリフレッシュ用アドレスが出力されます。
CLK	1	入 力	単相のクロック入力。 クロック入力が高レベル("1"レベルまたは"0"レベル継続)になるとMPUは動作を停止し、そのときの状態を保持します。
D0~D7	8	入出力 3ステート	8ビットの双方向性データバス。
INT	1	入 力	マスカブル割り込み要求信号。 割り込みは周辺LSIから起動されます。ソフトウェアによって、割り込み許可用フリップフロップ(IFF)が"1"にセットされていれば受け付けられます。INTは通常ワイヤードオアで使用され、その場合はプルアップ抵抗を外部に付加します。
NMI	1	入 力	ノンマスカブル割り込み要求信号。 この割り込み要求は、マスカブル割り込みより優先度が高く、割り込み許可用フリップフロップ(IFF)の状態に依存しません。
HALT	1	出 力	ホールド信号。 MPUがHALT命令を実行し、ホールド状態になると"0"が出力されます。
MREQ	1	出 力 3ステート	メモリリクエスト信号。 メモリアクセスのための有効アドレスがアドレスバスに乗っているときに"0"が出力されます。また、メモリリフレッシュ期間中もRFSH信号とともに"0"となります。
IORQ	1	出 力 3ステート	入出力リクエスト信号。 入出力動作で入出力のためのアドレスがアドレスバスの下位8ビット(A0~A7)に乗っているときに"0"が出力されます。また、IORQ信号は割り込みアクノリッジ時にMT信号とともに出力され、割り込み応答ベクトルをデータバス上に乗せてもよいことを周辺LSIに知らせます。
RFSH	1	出 力	リフレッシュ信号。 ダイナミックメモリのリフレッシュ用アドレスがアドレスバスの下位7ビットに乗っているとき"0"が出力されます。このとき、MREQ信号もアクティブ状態("0")になります。
MT	1	出 力	マシンサイクル1を示す信号。 命令のオペコードフェッチサイクルでMREQとともに"0"が出力されます。2バイトのオペコード実行時には、オペコードフェッチごとに出力されます。マスカブル割り込みアクノリッジサイクルではIORQ信号とともに出力されます。
RESET	1	入 力	リセット信号。 RESET信号は、MPUの初期化を行う信号で少なくとも3クロック期間アクティブ状態("0")にしなければなりません。
BUSREQ	1	入 力	バスリクエスト信号。 BUSREQ信号はMPUのアドレスバス、データバス、MREQ、IORQ、RD、WRを高インピーダンス状態にすることを要求する信号です。BUSREQ信号は通常ワイヤードオアで使用され、その場合はプルアップ抵抗を外部に付加します。
WAIT	1	入 力	ウェイト信号。 WAIT信号は、MPUに対して指定されたメモリあるいは周辺LSIがデータ転送準備ができていないことを知らせます。WAIT信号が"0"である限り、MPUはウェイト状態を継続します。
BUSACK	1	出 力	バスアクノリッジ信号。 BUSREQ信号を受け付けて、周辺LSIに対して、MPUのアドレスバス、データバス、MREQ、IORQ、RD、WRが高インピーダンス状態になったことを知らせます。
WR	1	出 力 3ステート	ライト信号。 指定したメモリあるいは周辺LSIに格納すべきデータがMPUデータバスに乗っているとき出力されます。
RD	1	出 力 3ステート	リード信号。 MPUがメモリまたは周辺LSIからデータを受入れ可能な期間、"0"が出力されます。指定された周辺LSIあるいはメモリのデータをこの信号でゲートし、MPUのデータバスに乗せることができます。
NC (PLCCのみ)	4	-	内部には接続されていません。 オープンで使用して下さい。
Vcc	1	電 源	+5V
Vss	1	電 源	0V

PARTS LIST

PART NO. : 837-7996B

DESCRIPTION : IC BD GG MAIN EUROPE B

LINE	LOCATE	DNO OR	PART NO.	DESCRIPTION
61.00	R14	126	476-2201-J-10	RES CHIP 200 OHM 1/10W 5%
62.00	R17	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
63.00	R18	134	476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
64.00	R20 (SOLDER)	129	476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
65.00	R21 (SOLDER)	129	476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
66.00	R22 (SOLDER)	134	476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
67.00	R23 (SOLDER)	129	476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
68.00	R24 (SOLDER)	129	476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
69.00	R25 (SOLDER)	134	476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
70.00	R26	138	476-2473-J-10	RES CHIP 47KOHM 1/10W 5%
71.00	R27	138	476-2473-J-10	RES CHIP 47KOHM 1/10W 5%
72.00	R28	910	NOT USED	NOT USED
73.00	R29	130	476-2182-J-10	RES CHIP 1.8KOHM 1/10W 5%
74.00	R30	130	476-2182-J-10	RES CHIP 1.8KOHM 1/10W 5%
75.00	R31	139	476-2104-J-10	RES CHIP 100KOHM 1/10W 5%
76.00	R32	139	476-2104-J-10	RES CHIP 100KOHM 1/10W 5%
77.00	R33	172	476-2303-J-10	RES CHIP 30KOHM 1/10W 5%
78.00	R34	135	476-2203-J-10	RES CHIP 20KOHM 1/10W 5%
79.00	R35	125	476-2510-J-10	RES CHIP 51 OHM 1/10W 5%
80.00	R36	148	476-2563-F-10	RES CHIP 56KOHM 1/10W 1%
81.00	R37	146	476-2303-F-10	RES CHIP 30KOHM 1/10W 1%
82.00	R38	125	476-2510-J-10	RES CHIP 51 OHM 1/10W 5%
83.00	R39	143	476-2471-F-10	RES CHIP 470 OHM 1/10W 1%
84.00	R40	143	476-2471-F-10	RES CHIP 470 OHM 1/10W 1%
85.00	R41	131	476-2222-J-10	RES CHIP 2.2KOHM 1/10W 5%
86.00	R42	140	476-2244-J-10	RES CHIP 240KOHM 1/10W 5%
87.00	R43	136	476-2223-J-10	RES CHIP 22KOHM 1/10W 5%
88.00	R44	136	476-2223-J-10	RES CHIP 22KOHM 1/10W 5%
89.00	R45	142	476-2105-J-10	RES CHIP 1MOHM 1/10W 5%
90.00	R46	136	476-2223-J-10	RES CHIP 22KOHM 1/10W 5%
91.00	R47	136	476-2223-J-10	RES CHIP 22KOHM 1/10W 5%
92.00	R48 (SOLDER)	134	476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
93.00	R49 (SOLDER)	134	476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
94.00	R50	174	476-2912-F-10	RES CHIP 9.1KOHM 1/10W 1%
95.00	R51	173	476-2112-F-10	RES CHIP 1.1KOHM 1/10W 1%
96.00	R52	175	476-2302-F-10	RES CHIP 3KOHM 1/10W 1%
97.00	R53 (SOLDER)	171	476-2122-J-10	RES CHIP 1.2KOHM 1/10W 5%
98.00	R54	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
99.00	R55	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
100.00	R56	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
101.00	R57	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
102.00	R58	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
103.00	R59	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
104.00	R60 (SOLDER)	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
105.00	R61 (SOLDER)	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
106.00	R62 (SOLDER)	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
107.00	R63 (SOLDER)	127	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
108.00	R64	910	NOT USED	NOT USED
109.00	C1	165	150-0311	CAP E CHIP 33UF 6.3V M
110.00	C3	163	150-0308	CAP E CHIP 10UF 6.3V M
111.00	C4	157	151-0265	CAP CER CP 0.1UF 25V ZF 2125
112.00	C5	157	151-0265	CAP CER CP 0.1UF 25V ZF 2125
113.00	C6	163	150-0308	CAP E CHIP 10UF 6.3V M
114.00	C7	157	151-0265	CAP CER CP 0.1UF 25V ZF 2125
115.00	C8 (SOLDER)	158	151-0266	CAP CER CP 0.33UF 25V Z F 3216
116.00	C9 (SOLDER)	158	151-0266	CAP CER CP 0.33UF 25V Z F 3216
117.00	C10 (SOLDER)	158	151-0266	CAP CER CP 0.33UF 25V Z F 3216
118.00	C11 (SOLDER)	158	151-0266	CAP CER CP 0.33UF 25V Z F 3216
119.00	C12 (SOLDER)	157	151-0265	CAP CER CP 0.1UF 25V ZF 2125
120.00	C14	157	151-0265	CAP CER CP 0.1UF 25V ZF 2125

PARTS LIST

PART NO. : 837-7996B

DESCRIPTION : IC BD GG MAIN EUROPE B

LINE	LOCATE	DNO OR	PART NO.	DESCRIPTION
1.00		1	171-6101A	PC BD GG MAIN EUROPE
2.00	IC1	101	315-0545	IC Z80A C-MOS SOP TMP84C00AM-6
3.00	IC2	102	315-5377	IC CUSTOM CHIP VDP GG QFP
4.00	IC3	103	315-5378B	IC CUSTOM CHIP SCA GG QFP
5.00	IC4	104 1	315-0546	IC UPD4364G-15L SOP 28P
6.00	IC4	104 2	315-0611	IC FCB61C65L-70T SOP 28P
7.00	IC5 (SOLDER)	105	315-0547	IC HM65256BLFP-12 SOP 28P
8.00	IC6 (SOLDER)	106	313-5134	IC UPC358G2 SOP 8P
9.00	Q1	108	482-5126	XSTR 2SC1623 L5..7 CHIP
10.00	Q2	910	NOT USED	NOT USED
11.00	Q3 (SOLDER)	109	482-5127	XSTR 2SD1614 CHIP
12.00	Q4 (SOLDER)	109	482-5127	XSTR 2SD1614 CHIP
13.00	Q5	108	482-5126	XSTR 2SC1623 L5..7 CHIP
14.00	Q6	108	482-5126	XSTR 2SC1623 L5..7 CHIP
15.00	Q7	108	482-5126	XSTR 2SC1623 L5..7 CHIP
16.00	Q8	107	482-5125	XSTR 2SA812 M5..7 CHIP
17.00	Q9	108	482-5126	XSTR 2SC1623 L5..7 CHIP
18.00	Q10	107	482-5125	XSTR 2SA812 M5..7 CHIP
19.00	Q11	108	482-5126	XSTR 2SC1623 L5..7 CHIP
20.00	FB1	910	NOT USED	NOT USED
21.00	LD1 (SOLDER)	110	390-5308	LED SLR 34-VT3F
22.00	D1	111	481-5072	DIODE 1SS184 CHIP
23.00	D2	111	481-5072	DIODE 1SS184 CHIP
24.00	D3	111	481-5072	DIODE 1SS184 CHIP
25.00	D4	111	481-5072	DIODE 1SS184 CHIP
26.00	X1	112	230-5066	XTAL OSC 32.215905M 100PPM
27.00	GN1	113	209-5037	CONN 45P FOR GG 01-176914-1
27.10	CN1	113	209-5037-01	CONN 45P FOR GG 01
28.00	CN2	114	209-5038	CONN 10P FOR GG HDC-0492
29.00	CN3	115	212-5304	CONN 6P FOR GG 178094-6
30.00	CN4	116	212-5305	CONN 9P FOR GG 178094-9
31.00	FU1	117	514-5040	FUSE THERMAL SMO95B0
32.00	FU2	117	514-5040	FUSE THERMAL SMO95B0
33.00	1	118	048-0001	EYLET 3.5*7
34.00	2	118	048-0001	EYLET 3.5*7
35.00	EM1	119	271-0007	EMI FILTER STX222MB
36.00	EM2	119	271-0007	EMI FILTER STX222MB
37.00	EM3	119	271-0007	EMI FILTER STX222MB
38.00	EM4	119	271-0007	EMI FILTER STX222MB
39.00	EM5	119	271-0007	EMI FILTER STX222MB
40.00	EM6	119	271-0007	EMI FILTER STX222MB
41.00	EM7	119	271-0007	EMI FILTER STX222MB
42.00	EM8	119	271-0007	EMI FILTER STX222MB
43.00	L1	120	271-0017	BEADS INDUCTOR FBA04VA900AB-00
44.00	L3	121	180-5073	P.COIL CHIP 100UH LEM4532T101K
45.00	L2	122	180-5077	CHOKE COIL 105UH KI-1589
46.00	T1	123	560-5172	INVERTER XFMR KI-1588
47.00	VR1	124	220-5339	VOL CONT 20KB RK09J11TO
48.00	R1	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
49.00	R2	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
50.00	R3 (SOLDER)	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
51.00	R4 (SOLDER)	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
52.00	R5 (SOLDER)	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
53.00	R6 (SOLDER)	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
54.00	R7 (SOLDER)	141	476-2474-J-10	RES CHIP 470KOHM 1/10W 5%
55.00	R8 (SOLDER)	141	476-2474-J-10	RES CHIP 470KOHM 1/10W 5%
56.00	R9 (SOLDER)	141	476-2474-J-10	RES CHIP 470KOHM 1/10W 5%
57.00	R10 (SOLDER)	141	476-2474-J-10	RES CHIP 470KOHM 1/10W 5%
58.00	R11	128	476-2471-J-10	RES CHIP 470 OHM 1/10W 5%
59.00	R12 (SOLDER)	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
60.00	R13	132	476-2302-J-10	RES CHIP 3KOHM 1/10W 5%

PARTS LIST

PART NO. : 837-7996B

DESCRIPTION : IC BD GG MAIN EUROPE B

LINE	LOCATE	DNO OR	PART NO.	DESCRIPTION
176.00	C70	151	151-0291	CAP CER CP 39PF 50V K SL 160
177.00	C71	151	151-0291	CAP CER CP 39PF 50V K SL 160
178.00	C72	151	151-0291	CAP CER CP 39PF 50V K SL 160
179.00	C73	151	151-0291	CAP CER CP 39PF 50V K SL 160
180.00	C74	151	151-0291	CAP CER CP 39PF 50V K SL 160
181.00	C75	910	NOT USED	NOT USED
182.00	C76	177	151-0307	CAP CER CP 0.022UF 50V ZF212
183.00	C77	177	151-0307	CAP CER CP 0.022UF 50V ZF212
184.00	C78	178	151-0298	CAP CER CP 100PF 50V J SL 212
185.00	C79	910	NOT USED	NOT USED
186.00	C80	157	151-0265	CAP CER CP 0.1UF 25V ZF 212
187.00	C81	177	151-0307	CAP CER CP 0.022UF 50V ZF212
188.00	C82	179	151-0320	CAP CER CP 68PF 50V J CH 212
189.00	C83	181	151-0323	CAP CER CP 33PF 50V K SL 212
190.00	C84	182	151-0340	CAP CER CP 5PF 50V D CH 212
191.00	C85	181	151-0323	CAP CER CP 33PF 50V K SL
192.00		930	NOTE#1	NOTE LINE
193.00		931	NOTE#2	NOTE LINE
194.00		932	NOTE#3	NOTE LINE

PARTS LIST

PART NO. : 837-7996B

DESCRIPTION : IC BD GG MAIN EUROPE B

LINE	LOCATE		DNO OR PART NO.	DESCRIPTION
121.00	C15	(SOLDER)	149 151-0289	CAP CER CP 10PF 50V D CH 212
122.00	C16	(SOLDER)	149 151-0289	CAP CER CP 10PF 50V D CH 212
123.00	C17		170 1 153-0090	CAP TANT CHIP 1UF 10V
124.00	C17		170 2 153-0086	CAP TANT CHIP 1UF 16V
125.00	C18		155 151-0264	CAP CER CP 8200PF 50V K B 212
126.00	C19	(SOLDER)	157 151-0265	CAP CER CP 0.1UF 25V ZF 212
127.00	C20	(SOLDER)	170 1 153-0090	CAP TANT CHIP 1UF 10V
128.00	C20	(SOLDER)	170 2 153-0086	CAP TANT CHIP 1UF 16V
129.00	C21		170 1 153-0090	CAP TANT CHIP 1UF 10V
130.00	C21		170 2 153-0086	CAP TANT CHIP 1UF 16V
131.00	C22		155 151-0264	CAP CER CP 8200PF 50V K B 212
132.00	C23	(SOLDER)	170 1 153-0090	CAP TANT CHIP 1UF 10V
133.00	C23	(SOLDER)	170 2 153-0086	CAP TANT CHIP 1UF 16V
134.00	C24		154 151-0263	CAP CER CP 2200PF 50V K B 212
135.00	C25		154 151-0263	CAP CER CP 2200PF 50V K B 212
136.00	C26		154 151-0263	CAP CER CP 2200PF 50V K B 212
137.00	C27		154 151-0263	CAP CER CP 2200PF 50V K B 212
138.00	C28		154 151-0263	CAP CER CP 2200PF 50V K B 212
139.00	C29		154 151-0263	CAP CER CP 2200PF 50V K B 212
140.00	C30		154 151-0263	CAP CER CP 2200PF 50V K B 212
141.00	C31		167 150-0313	CAP E CHIP 100UF 6.3V M
142.00	C32		169 152-0177	CAP MP 0.1UF 100V 10%
143.00	C33		159 151-0272	CAP CER 270PF 2KV SL
144.00	C34		157 151-0265	CAP CER CP 0.1UF 25V ZF 212
145.00	C35		162 150-0307	CAP E CHIP 4.7UF 35V
146.00	C36		157 151-0265	CAP CER CP 0.1UF 25V ZF 212
147.00	C37		166 150-0318	CAP E CHIP 68UF 6.3V
148.00	C38		157 151-0265	CAP CER CP 0.1UF 25V ZF 212
149.00	C39		168 150-0319	CAP E CHIP 100UF 4V
150.00	C40		157 151-0265	CAP CER CP 0.1UF 25V ZF 212
151.00	C41		157 151-0265	CAP CER CP 0.1UF 25V ZF 212
152.00	C42		156 151-0271	CAP CER CP 0.01UF 50V ZF 212
153.00	C43		156 151-0271	CAP CER CP 0.01UF 50V ZF 212
154.00	C44		161 150-0317	CAP E CHIP 0.47UF 50V
155.00	C45		161 150-0317	CAP E CHIP 0.47UF 50V
156.00	C46		152 151-0270	CAP CER CP 47PF 50V K SL 212
157.00	C47		152 151-0270	CAP CER CP 47PF 50V K SL 212
158.00	C48		163 150-0308	CAP E CHIP 10UF 6.3V M
159.00	C49		164 150-0309	CAP E CHIP 22UF 6.3V M
160.00	C50		157 151-0265	CAP CER CP 0.1UF 25V ZF 212
161.00	C51		157 151-0265	CAP CER CP 0.1UF 25V ZF 212
162.00	C52		160 151-0286	CAP CER CHIP 0.47UF 16V Z F
163.00	C53		160 151-0286	CAP CER CHIP 0.47UF 16V Z F
164.00	C58	(SOLDER)	153 151-0290	CAP CER CP 1200PF 50V K B 212
165.00	C59		151 151-0291	CAP CER CP 39PF 50V K SL 160
166.00	C60		151 151-0291	CAP CER CP 39PF 50V K SL 160
167.00	C61		151 151-0291	CAP CER CP 39PF 50V K SL 160
168.00	C62		151 151-0291	CAP CER CP 39PF 50V K SL 160
169.00	C63		151 151-0291	CAP CER CP 39PF 50V K SL 160
170.00	C64		151 151-0291	CAP CER CP 39PF 50V K SL 160
171.00	C65		151 151-0291	CAP CER CP 39PF 50V K SL 160
172.00	C66		151 151-0291	CAP CER CP 39PF 50V K SL 160
173.00	C67		151 151-0291	CAP CER CP 39PF 50V K SL 160
174.00	C68		151 151-0291	CAP CER CP 39PF 50V K SL 160
175.00	C69	(SOLDER)	150 151-0288	CAP CER CP 39PF 50V K SL 212

PARTS LIST

PART NO. : 837-7996
 DESCRIPTION : IC BD GG MAIN EUROPE

LINE	LOCATE	DNO OR PART NO.	DESCRIPTION
173.00	C67	151 151-0291	CAP CER CP 39PF 50V K SL 160
174.00	C68	151 151-0291	CAP CER CP 39PF 50V K SL 160
175.00	C69 (SOLDER)	150 151-0288	CAP CER CP 39PF 50V K SL 212
176.00	C70	151 151-0291	CAP CER CP 39PF 50V K SL 160
177.00	C71	151 151-0291	CAP CER CP 39PF 50V K SL 160
178.00	C72	151 151-0291	CAP CER CP 39PF 50V K SL 160
179.00	C73	151 151-0291	CAP CER CP 39PF 50V K SL 160
180.00	C74	151 151-0291	CAP CER CP 39PF 50V K SL 160
181.00	C75	180 151-0322	CAP CER CP 120PF 50V J CH 160
182.00	C76	177 151-0307	CAP CER CP 0.022UF 50V ZF212
183.00	C77	177 151-0307	CAP CER CP 0.022UF 50V ZF212
184.00	C78	178 151-0298	CAP CER CP 100PF 50V J SL 212
185.00	C79	178 NOT USED	NOT USED
186.00	C80	157 151-0265	CAP CER CP 0.1UF 25V ZF 212
187.00	C81	177 151-0307	CAP CER CP 0.022UF 50V ZF212
188.00	C82	179 151-0320	CAP CER CP 68PF 50V J CH 212
189.00	C83	181 151-0323	CAP CER CP 33PF 50V K SL 212
190.00	C84	182 151-0340	CAP CER CP 5PF 50V D CH 212
191.00	C85	181 151-0323	CAP CER CP 33PF 50V K SL 212
192.00		930 NOTE#1	NOTE LINE
193.00		931 NOTE#2	NOTE LINE
194.00		932 NOTE#3	NOTE LINE

PARTS LIST

PART NO. : 837-7996

DESCRIPTION : IC BD GG MAIN EUROPE

LINE	LOCATE	DNO OR PART NO.	DESCRIPTION
116.00	C9 (SOLDER)	158 151-0266	CAP CER CP 0.33UF 25V Z F 3216
117.00	C10 (SOLDER)	158 151-0266	CAP CER CP 0.33UF 25V Z F 3216
118.00	C11 (SOLDER)	158 151-0266	CAP CER CP 0.33UF 25V Z F 3216
119.00	C12 (SOLDER)	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
120.00	C14	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
121.00	C15 (SOLDER)	149 151-0289	CAP CER CP 10PF 50V D CH 2125
121.10	C16 (SOLDER)	149 151-0289	CAP CER CP 10PF 50V D CH 2125
122.00	C16 (SOLDER)	176 151-0316	CAP CER CP 20PF 50V J CH 2125
123.00	C17	170 1 153-0090	CAP TANT CHIP 1UF 10V
124.00	C17	170 2 153-0086	CAP TANT CHIP 1UF 16V
125.00	C18	155 151-0264	CAP CER CP 8200PF 50V K B 2125
126.00	C19 (SOLDER)	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
127.00	C20 (SOLDER)	170 1 153-0090	CAP TANT CHIP 1UF 10V
128.00	C20 (SOLDER)	170 2 153-0086	CAP TANT CHIP 1UF 16V
129.00	C21	170 1 153-0090	CAP TANT CHIP 1UF 10V
130.00	C21	170 2 153-0086	CAP TANT CHIP 1UF 16V
31.00	C22	155 151-0264	CAP CER CP 8200PF 50V K B 2125
132.00	C23 (SOLDER)	170 1 153-0090	CAP TANT CHIP 1UF 10V
133.00	C23 (SOLDER)	170 2 153-0086	CAP TANT CHIP 1UF 16V
134.00	C24	154 151-0263	CAP CER CP 2200PF 50V K B 2125
135.00	C25	154 151-0263	CAP CER CP 2200PF 50V K B 2125
136.00	C26	154 151-0263	CAP CER CP 2200PF 50V K B 2125
137.00	C27	154 151-0263	CAP CER CP 2200PF 50V K B 2125
138.00	C28	154 151-0263	CAP CER CP 2200PF 50V K B 2125
139.00	C29	154 151-0263	CAP CER CP 2200PF 50V K B 2125
140.00	C30	154 151-0263	CAP CER CP 2200PF 50V K B 2125
141.00	C31	167 150-0313	CAP E CHIP 100UF 6.3V M
142.00	C32	169 152-0177	CAP MP 0.1UF 100V 10%
143.00	C33	159 151-0272	CAP CER 270PF 2KV SL
144.00	C34	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
145.00	C35	162 150-0307	CAP E CHIP 4.7UF 35V
146.00	C36	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
147.00	C37	166 150-0318	CAP E CHIP 68UF 6.3V
148.00	C38	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
149.00	C39	168 150-0319	CAP E CHIP 100UF 4V
50.00	C40	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
151.00	C41	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
152.00	C42	156 151-0271	CAP CER CP 0.01UF 50V ZF 2125
153.00	C43	156 151-0271	CAP CER CP 0.01UF 50V ZF 2125
154.00	C44	161 150-0317	CAP E CHIP 0.47UF 50V
155.00	C45	161 150-0317	CAP E CHIP 0.47UF 50V
156.00	C46	152 151-0270	CAP CER CP 47PF 50V K SL 2125
157.00	C47	152 151-0270	CAP CER CP 47PF 50V K SL 2125
158.00	C48	163 150-0308	CAP E CHIP 10UF 6.3V M
159.00	C49	164 150-0309	CAP E CHIP 22UF 6.3V M
160.00	C50	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
161.00	C51	157 151-0265	CAP CER CP 0.1UF 25V ZF 2125
162.00	C52	160 151-0286	CAP CER CHIP 0.47UF 16V Z F
163.00	C53	160 151-0286	CAP CER CHIP 0.47UF 16V Z F
164.00	C58 (SOLDER)	153 151-0290	CAP CER CP 1200PF 50V K B 2125
165.00	C59	151 151-0291	CAP CER CP 39PF 50V K SL 1608
166.00	C60	151 151-0291	CAP CER CP 39PF 50V K SL 1608
167.00	C61	151 151-0291	CAP CER CP 39PF 50V K SL 1608
168.00	C62	151 151-0291	CAP CER CP 39PF 50V K SL 1608
169.00	C63	151 151-0291	CAP CER CP 39PF 50V K SL 1608
170.00	C64	151 151-0291	CAP CER CP 39PF 50V K SL 1608
171.00	C65	151 151-0291	CAP CER CP 39PF 50V K SL 1608
172.00	C66	151 151-0291	CAP CER CP 39PF 50V K SL 1608

PART NO. : 837-7996

DESCRIPTION : IC BD GG MAIN EUROPE

LINE	LOCATE	DNO OR PART NO.	DESCRIPTION
56.00	R9 (SOLDER)	141 476-2474-J-10	RES CHIP 470KOHM 1/10W 5%
57.00	R10 (SOLDER)	141 476-2474-J-10	RES CHIP 470KOHM 1/10W 5%
58.00	R11	128 476-2471-J-10	RES CHIP 470 OHM 1/10W 5%
59.00	R12 (SOLDER)	133 476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
60.00	R13	132 476-2302-J-10	RES CHIP 3KOHM 1/10W 5%
61.00	R14	126 476-2201-J-10	RES CHIP 200 OHM 1/10W 5%
62.00	R17	133 476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
63.00	R18	134 476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
64.00	R20 (SOLDER)	129 476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
65.00	R21 (SOLDER)	129 476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
66.00	R22 (SOLDER)	134 476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
67.00	R23 (SOLDER)	129 476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
68.00	R24 (SOLDER)	129 476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
69.00	R25 (SOLDER)	134 476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
70.00	R26	138 476-2473-J-10	RES CHIP 47KOHM 1/10W 5%
71.00	R27	138 476-2473-J-10	RES CHIP 47KOHM 1/10W 5%
72.00	R28	910 NOT USED	NOT USED
73.00	R29	130 476-2182-J-10	RES CHIP 1.8KOHM 1/10W 5%
74.00	R30	130 476-2182-J-10	RES CHIP 1.8KOHM 1/10W 5%
75.00	R31	139 476-2104-J-10	RES CHIP 100KOHM 1/10W 5%
76.00	R32	139 476-2104-J-10	RES CHIP 100KOHM 1/10W 5%
77.00	R33	172 476-2303-J-10	RES CHIP 30KOHM 1/10W 5%
78.00	R34	135 476-2203-J-10	RES CHIP 20KOHM 1/10W 5%
79.00	R35	125 476-2510-J-10	RES CHIP 51 OHM 1/10W 5%
80.00	R36	148 476-2563-F-10	RES CHIP 56KOHM 1/10W 1%
81.00	R37	146 476-2303-F-10	RES CHIP 30KOHM 1/10W 1%
82.00	R38	125 476-2510-J-10	RES CHIP 51 OHM 1/10W 5%
83.00	R39	143 476-2471-F-10	RES CHIP 470 OHM 1/10W 1%
84.00	R40	143 476-2471-F-10	RES CHIP 470 OHM 1/10W 1%
85.00	R41	131 476-2222-J-10	RES CHIP 2.2KOHM 1/10W 5%
86.00	R42	140 476-2244-J-10	RES CHIP 240KOHM 1/10W 5%
87.00	R43	136 476-2223-J-10	RES CHIP 22KOHM 1/10W 5%
88.00	R44	136 476-2223-J-10	RES CHIP 22KOHM 1/10W 5%
89.00	R45	142 476-2105-J-10	RES CHIP 1MOHM 1/10W 5%
90.00	R46	136 476-2223-J-10	RES CHIP 22KOHM 1/10W 5%
91.00	R47	136 476-2223-J-10	RES CHIP 22KOHM 1/10W 5%
92.00	R48 (SOLDER)	134 476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
93.00	R49 (SOLDER)	134 476-2103-J-10	RES CHIP 10KOHM 1/10W 5%
94.00	R50	174 476-2912-F-10	RES CHIP 9.1KOHM 1/10W 1%
95.00	R51	173 476-2112-F-10	RES CHIP 1.1KOHM 1/10W 1%
96.00	R52	175 476-2302-F-10	RES CHIP 3KOHM 1/10W 1%
97.00	R53 (SOLDER)	171 476-2122-J-10	RES CHIP 1.2KOHM 1/10W 5%
98.00	R54	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
99.00	R55	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
100.00	R56	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
101.00	R57	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
102.00	R58	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
103.00	R59	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
104.00	R60 (SOLDER)	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
105.00	R61 (SOLDER)	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
106.00	R62 (SOLDER)	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
107.00	R63 (SOLDER)	127 476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
108.00	R64	910 NOT USED	NOT USED
109.00	C1	165 150-0311	CAP E CHIP 33UF 6.3V M
110.00	C3	163 150-0308	CAP E CHIP 10UF 6.3V M
111.00	C4	157 151-0265	CAP CER CP 0.1UF 25V ZF 21%
112.00	C5	157 151-0265	CAP CER CP 0.1UF 25V ZF 21%
113.00	C6	163 150-0308	CAP E CHIP 10UF 6.3V M
114.00	C7	157 151-0265	CAP CER CP 0.1UF 25V ZF 21%
115.00	C8 (SOLDER)	158 151-0266	CAP CER CP 0.33UF 25V Z F 32%

PART NO. : 837-7996
 DESCRIPTION : IC BD GG MAIN EUROPE


LINE	LOCATE	DNO OR	PART NO.	DESCRIPTION
1.00		1	171-6101A	PC BD GG MAIN EUROPE
2.00	IC1	101	315-0545	IC Z80A C-MOS SOP TMP84C00AM
3.00	IC2	102	315-5377	IC CUSTOM CHIP VDP GG QFP
4.00	IC3	103	315-5378A	IC CUSTOM CHIP SCA GG QFP
5.00	IC4	104 1	315-0546	IC UPD4364G-15L SOP 28P
6.00	IC4	104 2	315-0611	IC FCB61C65L-70T SOP 28P
7.00	IC5 (SOLDER)	105	315-0547	IC HM65256BLEP-12 SOP 28P
8.00	IC6 (SOLDER)	106	313-5134	IC UPC358G2 SOP 8P
9.00	Q1	108	482-5126	XSTR 2SC1623 L5..7 CHIP
10.00	Q2	910	NOT USED	NOT USED
11.00	Q3 (SOLDER)	109	482-5127	XSTR 2SD1614 CHIP
12.00	Q4 (SOLDER)	109	482-5127	XSTR 2SD1614 CHIP
13.00	Q5	108	482-5126	XSTR 2SC1623 L5..7 CHIP
14.00	Q6	108	482-5126	XSTR 2SC1623 L5..7 CHIP
15.00	Q7	108	482-5126	XSTR 2SC1623 L5..7 CHIP
16.00	Q8	107	482-5125	XSTR 2SA812 M5..7 CHIP
17.00	Q9	108	482-5126	XSTR 2SC1623 L5..7 CHIP
18.00	Q10	107	482-5125	XSTR 2SA812 M5..7 CHIP
19.00	Q11	108	482-5126	XSTR 2SC1623 L5..7 CHIP
20.00	FB1	910	NOT USED	NOT USED
21.00	LD1 (SOLDER)	110	390-5308	LED SLR 34-VT3F
22.00	D1	111	481-5072	DIODE 1SS184 CHIP
23.00	D2	111	481-5072	DIODE 1SS184 CHIP
24.00	D3	111	481-5072	DIODE 1SS184 CHIP
25.00	D4	111	481-5072	DIODE 1SS184 CHIP
26.00	X1	112	230-5066	XTAL OSC 32.215905M 100PPM
27.00	CN1	113	209-5037	CONN 45P FOR GG 0-176914-1
27.10	CN1	113	209-5037-01	CONN 45P FOR GG 01
28.00	CN2	114	209-5038	CONN 10P FOR GG HDC-0492
29.00	CN3	115	209-5039	CHANGE TO 212-5304
30.00	CN4	116	209-5041	CHANGE TO 212-5305
30.10	CN3	115	212-5304	CONN 6P FOR GG 178094-6
30.20	CN4	116	212-5305	CONN 9P FOR GG 178094-9
31.00	FU1	117	514-5040	FUSE THERMAL SMO95BO
32.00	FU2	117	514-5040	FUSE THERMAL SMO95BO
33.00	1	118	048-0001	EYLET 3.5*7
34.00	2	118	048-0001	EYLET 3.5*7
35.00	EM1	119	271-0007	EMI FILTER STX222MB
36.00	EM2	119	271-0007	EMI FILTER STX222MB
37.00	EM3	119	271-0007	EMI FILTER STX222MB
38.00	EM4	119	271-0007	EMI FILTER STX222MB
39.00	EM5	119	271-0007	EMI FILTER STX222MB
40.00	EM6	119	271-0007	EMI FILTER STX222MB
41.00	EM7	119	271-0007	EMI FILTER STX222MB
42.00	EM8	119	271-0007	EMI FILTER STX222MB
43.00	L1	120	271-0017	BEADS INDUCTOR FBA04VA900AB-1
44.00	L3	121	180-5073	P.COIL CHIP 100UH LEM4532T10
45.00	L2	122	180-5077	CHOKE COIL 105UH K1-1589
46.00	T1	123	560-5172	INVERTER XFMR K1-1588
47.00	VR1	124	220-5339	VOL CONT 20KB RK09J11TO
48.00	R1	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
49.00	R2	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
50.00	R3 (SOLDER)	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
51.00	R4 (SOLDER)	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
52.00	R5 (SOLDER)	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
53.00	R6 (SOLDER)	133	476-2472-J-10	RES CHIP 4.7KOHM 1/10W 5%
54.00	R7 (SOLDER)	141	476-2474-J-10	RES CHIP 470KOHM 1/10W 5%
55.00	R8 (SOLDER)	141	476-2474-J-10	RES CHIP 470KOHM 1/10W 5%

GAME GEAR


EUROPE

PARTS LIST OF PCB


TDA2822M






SCHEMATIC DIAGRAM




8 lead Plastic Minidip
4 + 4 lead Powerdip











プラスチック・SOP, 16ピン
(FPT-16P-M02)



単位: mm (inches)



(FPT-28P-M02)





單位：mm (inches)

μ PC1251/358

電子接頭 (Top View)


11. C 1251 D. 1251 C. 1251 G

11'C358C. 358G







MAIN BOARD IC5 1/1
IC HM6256BLFP-12

■ピン配置



■ ブロックダイアグラム



マーキング方法



SEGA

315-5378B


ロットNo


PIN NO.	PIN NAME	PIN NO.	PIN NAME	PIN NO.	PIN NAME	PIN NO.	PIN NAME
1	GND	26	RESO	51	DW	76	PC4
2	VDD	27	NLED	52	VDD	77	PC5
3	XTL1	28	GND	53	GND	78	PC6
4	XTL2	29	VDD	54	CLB1	79	VDD
5	CCLK	30	VREF	55	CLA1	80	GND
6	VCLK	31	VONF	56	CLB2	81	D7D
7	NUP	32	VRES	57	CLA2	82	D6D
8	NDW	33	SNDN	58	CLB3	83	D5C
9	NLE	34	SND3	59	CLA3	84	D4P
10	NR1	35	SND2	60	TPR1	85	D3P
11	NTL	36	SND1	61	TPR2	86	D2P
12	NTR	37	SNDL	62	A	87	D1P
13	NPS	38	SNDR	63	SAMP	88	D0D
14	CPA0	39	TEST	64	NLCD	89	AAR2
15	CPA1	40	GND	65	NTV	90	A9R1
16	CPA2	41	DB	66	NGG	91	A8A3
17	CPA3	42	P3	67	NNM1	92	A7B3
18	CPB	43	P2	68	NM1	93	A6A2
19	NTSC	44	P4	69	IORQ	94	A5B2
20	H488	45	P1	70	NWR	95	A4A1
21	HBNK	46	CL2	71	NRD	96	A3B1
22	VBNK	47	DO2	72	PC0	97	A2DW
23	NHL	48	DO4	73	PC1	98	A1D3
24	NJAP	49	DO1	74	PC2	99	A0D1
25	SPON	50	DO3	75	PC3	100	XCLK

PIN ASSIGN (TOP VIEW)




端子先端形状詳細図





80 Pin Plastic FLAT




PARTS LIST


PART NO. : 837-7998
DESCRIPTION : IC BD GG SOUND EUROPE

LINE	LOCATE	DNO OR	PART NO.	DESCRIPTION
1.00		1	171-6103A	PC BD GG SOUND EUROPE
2.00	J1	102	210-5061	CONN MINI JACK HSJ0873-01-140
3.00	CN1	103	600-5910	WIRE HARN GP FOR GG 60MM
4.00	CN2	104	209-5040	CHANGE TO 212-5301-02
4.10	CN2	104	212-5301-02	CONN M MT AMP CT 2P 173981-2
5.00	VR1	105	220-5343	SW VOL CONT 10KOHM K102J0Z25
6.00	IC1	101	313-5141	IC TDA2822M
7.00	R1	108	476-2563-J-10	RES CHIP 56KOHM 1/10W 5%
8.00	R2	108	476-2563-J-10	RES CHIP 56KOHM 1/10W 5%
9.00	R3	106	476-24R7-J-10	RES CHIP 4.7 OHM 1/10W 5%
10.00	R4	106	476-24R7-J-10	RES CHIP 4.7 OHM 1/10W 5%
11.00	R5	107	476-2101-J-10	RES CHIP 100 OHM 1/10W 5%
12.00	R6	107	476-2101-J-10	RES CHIP 100 OHM 1/10W 5%
13.00	C1	111	150-0313-01	CAP E CP 100UF 6.3V MV6.3VC10
14.00	C2	111	150-0313-01	CAP E CP 100UF 6.3V MV6.3VC10
15.00	C3	111	150-0313-01	CAP E CP 100UF 6.3V MV6.3VC10
16.00	C4	109	151-0265	CAP CER CP 0.1UF 25V ZF 212
17.00	C5	110	150-0312-01	CAP E CP 47UF 4V MV4VC47
18.00	C6	109	151-0265	CAP CER CP 0.1UF 25V ZF 212
19.00	C7	110	150-0312-01	CAP E CP 47UF 4V MV4VC47
20.00	C8	109	151-0265	CAP CER CP 0.1UF 25V ZF 212
21.00	LF1	112	270-5044	LINE FILTER(SDP-103C)

837-7997B(7/3)



Sold Side 部品面視半田面





部品面視部品面 Comp Side

MACHINE 機名	SUB-ASS'Y 組立番
	837-7995B
ALTERATIONS 改訂	

SEGA		SEGA ENTERPRISES, LTD.		THIS DRAWING WILL IN NO WAY BE COPIED. TO BE RETURNED ON DEMAND.		許可なく複写 複製等厳禁	
LIMITS UNLESS OTHERWISE SPECIFIED 一般公差		3RD QUAT. PROJ. DRAWING 第三角法		設計・製図	検図	検記	承認
		SCALE 尺量	X	松本			
		DIM. IN 単位	mm				
MATERIAL 材料	HEAT TREAT. 熱処理	FINISH 表面処理		REMARK 特殊指示		REV.	
IC BD 0A DC-DC CONU. EUROPE(8AB)				837-7997B(7/3)			
DESCRIPTION 名称				PART NO. 図書・部品番号			

837-7998 (2/3)


Sold Side 半田面視 半田面




部品面視 部品面 Comp Side

SEGA		SEGA ENTERPRISES, LTD.		THIS DRAWING WILL IN NO WAY BE COPIED. TO BE RETURNED ON DEMAND.		許可なく複写 複製等禁	
LIMITS UNLESS OTHERWISE SPECIFIED 一般公差		3RD QUAT PROJ. DRAWING 第三角法		設計・製図	検図	承認	承認
		SCALE 尺法	X	松本 大場		永	
		DIM. IN 単位	mm	58-91 59-91		59-91	
MATERIAL 材料		HEAT TREAT. 熱処理		FINISH 表面処理		REMARK 特殊指示	REV.
IC BD 88 SOUND EUROPE						837-7998 (2/3)	
DESCRIPTION 名称						PART NO. 図番・部品番号	

MACHINE 機名	SUB-ASS'Y. 組立番
	837-7995
ALTERATIONS 改訂	



Sold Side 半田面視 半田面





部品面視 部品面 Comp Side

MACHINE 機名	SUB-ASSY. 部品番
	837-7995 B
ALTERATIONS 改訂	






837-7998B(2/3)



SEGA		SEGA ENTERPRISES, LTD.		THIS DRAWING WILL IN NO WAY BE COPIED. TO BE RETURNED ON DEMAND.				許可なく複写 複製等厳禁	
LIMITS UNLESS OTHERWISE SPECIFIED 一般公差		3RD QUAT. PROJ. DRAWING 第三角法		設計・製図	検図	検記	承認		
		SCALE 尺度	X	松本					
		DIM. IN 単位	mm						
MATERIAL 材料	HEAT TREAT. 熱処理	FINISH 表面処理	REMARK 特殊指示	REV.					
IC BD 01A SOUND EUROPE (SCA B)				837-7998B (2/3)					
DESCRIPTION 名称				PART NO. 図番・部品番号					

[illegible]







S o l d S i d e

		SEGA ENTERPRISES, LTD.		THIS DRAWING WILL IN NO WAY BE COPIED, TO BE DETERMINED BY DEMAND.		此可ク複製 決定される	
LIMITS UNLESS OTHERWISE SPECIFIED		3PO QUAT PROJ DRAWING		SCALE 1:1		DIM IN mm	
							
MATERIAL		HEAT TREAT.		FINISH		REMARK	
IC ED 88 MAIN EUROPE						237-7996 (2/4)	
DESCRIPTION						PART NO.	



371

 SEGA ENTERPRISES, LTD.		THIS DRAWING WILL IN NO WAY BE COPIED, TO BE RETURNED ON DEMAND.		許可なく複写 戻却を要す	
LIMITS UNLESS OTHERWISE SPECIFIED 一般公差		3RD QUAT PROJ DRAWING 第三分組 設計図		単位 単位 単位 単位	
		SCALE 比例	<input checked="" type="checkbox"/>	松本	
		DIM. IN 寸法	mm		
					
MATERIAL 材料	HEAT TREAT. 熱処理	FINISH 表面処理		REMARK 特記事項	REV.
IC BD 68 MAIN EUROPE (SCA)				837-7996B(3/4)	
DESCRIPTION 名称				PART NO. 14部・部品番号	

195NY 666-657

PARTS LIST

PART NO. : 837-7997

DESCRIPTION : IC BD GG DC-DC CONV. EUROPE

LINE	LOCATE	DNO OR	PART NO.	DESCRIPTION
1.00		1	171-6102A	PC BD GG DC-DC CONV. EUROPE
2.00	J1	111	210-5062	CONN DC JACK W/SW LGP4031-0300
3.00	CN1	108	600-5911	WIRE HARN 9P FOR GG GOMM
4.00	SW1	112	510-5028	SLIDE SW HSW1805-010010
5.00	IC1	101	313-5140	IC MB3775PF-G-BND SOP
6.00	Q1	102	482-5125	XSTR 2SA812 M5.1.7 CHIP
7.00	Q2 (SOLDER)	103	482-5126	XSTR 2SC1623 1.5.1.7 CHIP
8.00	Q3	104	482-5130	XSTR 2SB1301 2Q OR 2P CHIP
9.00	Q4 (SOLDER)	910	NOT USED	NOT USED
10.00	D1	106	481-5038	DIODE 1SR-35-100A AXIAL
11.00	D2	105	481-5071	DIODE HRF 22 CHIP
12.00	D3	105	481-5071	DIODE HRF 22 CHIP
13.00	D4 (SOLDER)	910	NOT USED	NOT USED
14.00	D5	910	NOT USED	NOT USED
15.00	D6 (SOLDER)	910	NOT USED	NOT USED
16.00	L1	113	180-5071	CHOKE COIL 1.2MH FL7H122J
17.00	L2	114 1	180-5072	CHOKE COIL 68UH TSL1110680K1R
18.00	L2	114 2	180-5083	CHOKE COIL 68UH A90-870-0
19.00	JV	115	271-0017	BEADS INDUCTOR FBA04VA900AB-00
20.00	JG	115	271-0017	BEADS INDUCTOR FBA04VA900AB-00
21.00	R1	122	476-2333-J-10	RES CHIP 33KOHM 1/10W 5%
22.00	R2	121	476-2273-J-10	RES CHIP 27KOHM 1/10W 5%
23.00	R3	117	476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
24.00	R4	119	476-2392-J-10	RES CHIP 3.9KOHM 1/10W 5%
25.00	R5 (SOLDER)	118	476-2222-J-10	RES CHIP 2.2KOHM 1/10W 5%
26.00	R6 (SOLDER)	117	476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
27.00	R7 (SOLDER)	129	476-2114-F-10	RES CHIP 110KOHM 1/10W 1%
28.00	R8 (SOLDER)	126	476-2432-F-10	RES CHIP 4.3KOHM 1/10W 1%
29.00	R9	123	476-2473-J-10	RES CHIP 47KOHM 1/10W 5%
30.00	R10 (SOLDER)	122	476-2333-J-10	RES CHIP 33KOHM 1/10W 5%
31.00	R11 (SOLDER)	120	476-2123-J-10	RES CHIP 12KOHM 1/10W 5%
32.00	R12	130	476-0361-J-04	RES CHIP 360 OHM 1/4W 5%
33.00	R13 (SOLDER)	116	476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
34.00	R14	128	476-2203-F-10	RES CHIP 20KOHM 1/10W 1%
35.00	R15	127	476-2682-F-10	RES CHIP 6.8KOHM 1/10W 1%
36.00	R16 (SOLDER)	910	NOT USED	NOT USED
37.00	R17 (SOLDER)	910	NOT USED	NOT USED
38.00	R18	125	476-2514-F-10	RES CHIP 510KOHM 1/10W 1%
39.00	R19	910	NOT USED	NOT USED
40.00	C1 (SOLDER)	139	153-0088	CAP TANT CP 0.68UF 16V 3216
41.00	C2	133	151-0265	CAP CER CP 0.1UF 25V ZF 2125
42.00	C3	134	151-0269	CAP CER CP 0.1UF 25V K 2125
43.00	C4 (SOLDER)	133	151-0265	CAP CER CP 0.1UF 25V ZF 2125
44.00	C5	135	150-0314	CAP E 22UF 35V M 35SP(X)22
45.00	C6	133	151-0265	CAP CER CP 0.1UF 25V ZF 2125
46.00	C7	131	151-0268	CAP CER CHIP 680PF K B 2125
47.00	C8	134	151-0269	CAP CER CP 0.1UF 25V K 2125
48.00	C9 (SOLDER)	132	NOT USED	NOT USED
49.00	C10	133	151-0265	CAP CER CP 0.1UF 25V ZF 2125
50.00	C11	136	150-0315	CAP E 100UF 25V M 25SP(X)100
51.00	C12 (SOLDER)	133	151-0265	CAP CER CP 0.1UF 25V ZF 2125
52.00	C13	137	150-0316	CAP E 820UF 6.3V M 6.3SP(X)820


PARTS LIST

PART NO. : 837-7997B


DESCRIPTION : IC BD GG DC-DC CONV. EUROPE B

LINE	LOCATE	DNO	OR	PART NO.	DESCRIPTION
1.00		1		171-6102A	PC BD GG DC-DC CONV. EUROPE
2.00	J1	111		210-5062	CONN DC JACK W/SW LGP4031-03
3.00	CN1	108		600-5911	WIRE HARN 9P FOR GG 60MM
4.00	SW1	112		510-5028	SLIDE SW HSW1805-010010
5.00	IC1	101		313-5140	IC MB3775PF-G-BND SOP
6.00	Q1	102		482-5125	XSTR 2SA812 M5..7 CHIP
7.00	Q2 (SOLDER)	103		482-5126	XSTR 2SC1623 L5..7 CHIP
8.00	Q3	104		482-5130	XSTR 2SB1301 ZQ OR ZP CHIP
9.00	Q4 (SOLDER)	910		NOT USED	NOT USED
10.00	D1	106		481-5038	DIODE 1SR-35-100A AXIAL
11.00	D2	105		481-5071	DIODE HRF 22 CHIP
12.00	D3	105		481-5071	DIODE HRF 22 CHIP
13.00	D4 (SOLDER)	910		NOT USED	NOT USED
14.00	D5	910		NOT USED	NOT USED
15.00	D6 (SOLDER)	910		NOT USED	NOT USED
16.00	L1	113		180-5071	CHOKE COIL 1.2MH FL7H122J
17.00	L2	114 1		180-5072	CHOKE COIL 68UH TSL1110680K11
18.00	L2	114 2		180-5083	CHOKE COIL 68UH A90-870-0
19.00	JV	115		271-0017	BEADS INDUCTOR FBA04VA900AB-0
20.00	JG	115		271-0017	BEADS INDUCTOR FBA04VA900AB-0
21.00	R1	122		476-2333-J-10	RES CHIP 33KOHM 1/10W 5%
22.00	R2	121		476-2273-J-10	RES CHIP 27KOHM 1/10W 5%
23.00	R3	117		476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
24.00	R4	119		476-2392-J-10	RES CHIP 3.9KOHM 1/10W 5%
25.00	R5 (SOLDER)	118		476-2222-J-10	RES CHIP 2.2KOHM 1/10W 5%
26.00	R6 (SOLDER)	117		476-2102-J-10	RES CHIP 1KOHM 1/10W 5%
27.00	R7 (SOLDER)	129		476-2114-F-10	RES CHIP 110KOHM 1/10W 1%
28.00	R8 (SOLDER)	126		476-2432-F-10	RES CHIP 4.3KOHM 1/10W 1%
29.00	R9	123		476-2473-J-10	RES CHIP 47KOHM 1/10W 5%
30.00	R10 (SOLDER)	122		476-2333-J-10	RES CHIP 33KOHM 1/10W 5%
31.00	R11 (SOLDER)	120		476-2123-J-10	RES CHIP 12KOHM 1/10W 5%
32.00	R12	130		476-0361-J-04	RES CHIP 360 OHM 1/4W 5%
33.00	R13 (SOLDER)	116		476-2221-J-10	RES CHIP 220 OHM 1/10W 5%
34.00	R14	128		476-2203-F-10	RES CHIP 20KOHM 1/10W 1%
35.00	R15	127		476-2682-F-10	RES CHIP 6.8KOHM 1/10W 1%
36.00	R16 (SOLDER)	910		NOT USED	NOT USED
37.00	R17 (SOLDER)	910		NOT USED	NOT USED
38.00	R18	125		476-2514-F-10	RES CHIP 510KOHM 1/10W 1%
39.00	R19	910		NOT USED	NOT USED
40.00	C1 (SOLDER)	139		153-0088	CAP TANT CP 0.68UF 16V 3216
41.00	C2	133		151-0265	CAP CER CP 0.1UF 25V ZF 2125
42.00	C3	134		151-0269	CAP CER CP 0.1UF 25V K 2125
43.00	C4 (SOLDER)	133		151-0265	CAP CER CP 0.1UF 25V ZF 2125
44.00	C5	135		150-0314	CAP E 22UF 35V M 35SP(X)22
45.00	C6	133		151-0265	CAP CER CP 0.1UF 25V ZF 2125
46.00	C7	131		151-0268	CAP CER CHIP 680PF K B 2125
47.00	C8	134		151-0269	CAP CER CP 0.1UF 25V K 2125
48.00	C9 (SOLDER)	132		NOT USED	NOT USED
49.00	C10	133		151-0265	CAP CER CP 0.1UF 25V ZF 2125
50.00	C11	136		150-0315	CAP E 100UF 25V M 25SP(X)100
51.00	C12 (SOLDER)	133		151-0265	CAP CER CP 0.1UF 25V ZF 2125
52.00	C13	137		150-0316	CAP E 820UF 6.3V M 6.3SP(X)820

837-7997 (7/3)




Sold Side 部品面視半田面



部品面視部品面 Comp Side

MACHINE	機名	SUB-ASS'Y	組立番
		837-7995	
ALTERATIONS		改訂	

SEGA		SEGA ENTERPRISES, LTD.		THIS DRAWING WILL IN NO WAY BE COPIED. TO BE RETURNED ON DEMAND.		許可なく複写 複製等厳禁	
LIMITS UNLESS OTHERWISE SPECIFIED 一投二視		3RD QUAT. PROJ. DRAWING 第三角法		設計・製図	検図	承認	承認
		SCALE 尺法	X	松本 大場			水永
		DIM. IN 単位	mm				
				5/8-'91	5/9-'91	5/9-'91	
MATERIAL 材料	HEAT TREAT. 熱処理	FINISH 表面処理		REMARK 特殊指示	REV.		
IC BD 08 DC-DC CONV. EUROPE				837-7997 (7/3)			
DESCRIPTION 名称				PART NO. 図番・部品番号			



IC3
SCA
(138 QFP)
315-5378A
* IC3におい2. 315-5378Bは
使用の場合、C75は未使用のため。

IC 80 50 MAIN EUROPE B 315-7996B
IC 80 50 MAIN EUROPE 315-7996B-57A

SEGA	SEGA ENTERPRISES, LTD.	REV
THIS DRAWING WILL BE THE PROPERTY OF SEGA. IT IS TO BE RETURNED ON DEMAND.		REV
PC 80 60 MAIN EUROPE		REV
DESCRIPTION		REV

